

TO ORDER CALL: +61 8 8260 2277 OR  
CONTACT YOUR LOCAL MANUTEC DEALER

## GREASE CAPS, STUDS, NUT-PIN-WASHER

2" Grease Cap (45.2mm)	GRSCAP2
2.5" Grease Cap (63.6mm)	GRSCAP2.5
2.5" US Grease Cap (62.2mm)	GRSCAP2.5US
3" Grease Cap (76.6mm)	GRSCAP3
HT Stud—30mm	HTSTUD30
HT Stud—55mm	HTSTUD55
HT Stud—80mm	HTSTUD80
Crown Nut (3/4" UNF)	CROWN
Nut, Pin, Washer Set	CROWNSET
7/16" UNF Stud Nuts	PWH-SNUTS
1/2" UNF Stud Nuts	PWF-SNUTS



## ACCESSORIES

Description	ID Code
Overcap HT 60mm	PWOCAP/HT60
Overcap HT 80mm	PWOCAP/HT80
Overcap Ford 70mm	PWOCAP/FORD
Overcap BMW 60mm	PWOCAP/BMW
Seal Guard (Round)	PWSEALGUARD
Stub Protector (Round)	PWAXLEPROT
Bearing Buddies	BEARBUD2-CR



Press Wheels  
Jockey Wheels  
Tyne Mounts  
Walking Wheels  
Extension Arms  
Gangs  
In-Frame  
Seed Tubes  
Packer Wheels  
Coulters  
Bearings  
Seals  
Tyres  
Rubber Wheels  
Springs  
U-Bolts  
Castors  
Brackets  
Clamps  
Spare Parts  
Wheels  
Wheel Centres  
Axles  
Overcaps  
Seal Guards  
Hubs  
Stubs  
Jerry Can Holders  
Gas Bottle Holders  
Easy Movers  
Fixed Arms  
Grease Caps  
Discs  
Suspension Bolts  
Planter Wheels  
Couplocks  
Adjustable Stands  
Adjustable Legs  
Anchors  
Boat Rollers  
Winches  
Caravan Legs  
Boat Wheels

**Manutec**  
AGRICULTURAL PRODUCTS

## AGRICULTURAL EQUIPMENT & TRAILER PARTS



## HUBS-STUBS-AXLES-COMPONENTS

### Hubs, Stubs, Axles

Manutec carries a range of standard hubs, stubs and axles to suit trailer, light agricultural and light industrial applications. Variants include:

- HT
- FORD
- LANDCRUISER
- NARROW HT
- COMMODORE

All hubs, stubs and axles are available in a range of configurations to meet most needs. Made to order units are also available. Bearing options include European, Japanese and Chinese Brands. Available as individual components or as matched sets.

A large range of accessories and components are also available to suit the hubs.


## HUBS

Hub	Coating	Bearing/Seal Option	
<b>Landcruiser</b> 6 Stud 1/2"UNF PCD6x140mm Flange 190mm Hub 60.9mm	Galv Painted  MaxCapacity 1500kg per pair	HT Bearings Ford/Slimline Bearings Standard Seal Marine Seal J/E/C Bearing Options	
<b>Holden -HT</b> 5 Stud 7/16"UNF PCD5x4.25" Flange 150mm Hub 60.9mm	Galv Painted  MaxCapacity 1450kg per pair	HT Bearings Standard Seal Marine Seal J/E/C Bearing Options Optional Grease Nipple	
<b>Commodore</b> 5 Stud 7/16"UNF PCD5x120mm Flange 150mm Hub 60.9mm	Galv Painted  MaxCapacity 1450kg per pair	HT Bearings Standard Seal Marine Seal J/E/C Bearing Options	
<b>Ford</b> 5 Stud 7/16"UNF PCD5x4.5" Flange 150mm Hub 60.9mm	Galv Painted  MaxCapacity 1450kg per pair	HT Bearings Ford/Slimline Bearings Standard Seal Marine Seal J/E/C Bearing Options	
<b>Narrow HT</b> 5 Stud 7/16"UNF PCD5x4.25" Flange 150mm Hub 60.9mm	Galv  MaxCapacity 1450kg per pair	HT Bearings Standard Seal Marine Seal J/E/C Bearing Options	

### Narrow HT Hub

The Narrow HT Hub is a specially designed hub for agricultural applications where a HT pattern hub is required on equipment where space or weight limitations exist. The Narrow HT Hub profile is shorter than a standard HT Hub (71mm vs 101mm) and is also 100% compatible with Manutec's Integral Hub press wheels.

## STUBS & AXLES

Axle Ø	Pattern	Finish	Length	MaxLoad (per pair) 14" Wheels	
39mm Round	HT	Black	8",10",12"	750kg LM	
40mm Round	HT/Narrow HT	Bright	6",9",10"	750kg LM	
40mm Round	HT/Narrow HT	Zinc	6",9",10"	750kg LM	
40mm Square	HT/Narrow HT	Black	8",9",10"	1000kg LM	
45mm Square	Ford	Black	10",12"	1450kg SL	
45mm Round	Ford	Black	12"	1450kg SL	
40mm Round	Integral	Zinc	6",9",10"	750kg LM	

Axle Ø	Pattern	Finish	Length	Max Load 14" Wheels
39mm Round	HT	Black	63"	750kg LM
39mm Round	HT	Black	64"	750kg LM
39mm Round	HT	Black	65"	750kg LM
39mm Round	HT	Black	66"	750kg LM
39mm Round	HT	Black	67"	750kg LM

Made to order Stubs and Axles are available on request.

Note: When calculating hub/stub or hub/axle load capacity. The lowest max of all separate components is used. If using 16" wheels capacity is reduced by a further 25%.  
 Eg. 39mm Round Axle, HT Hubs, LM Bearings, 14" Wheels = 750kg max load capacity.

## BEARINGS & SEALS

Description	ID Code
Bearing Set LM	LM67048/10,LM11949/10
Cone Set LM	LM67048,LM11949
Cup Set LM	LM67010,LM11910
Bearing Set Slimline	L68149/10,LM12749/10
Cone Set Slimline	L68149,LM12749
Cup Set Simline	L68110,LM12710
Standard Seal—LM	SLM28550
Standard Seal—Slimline	SSL28600
Marine Seal—Standard	SELM82100
Marine Seal—Slimline	SESLM82120

### BEARING OPTIONS

- Japanese
- European
- Chinese
- J/E/C

